

## Spray-Applied Polyurethane Foam Insulation Characteristics

Date of Application: \_\_\_\_\_

Manufacturer of Spray-applied Polyurethane Foam Insulation (SPF): \_\_\_\_\_

Approved under CCMC#: \_\_\_\_\_ for Insulation  Air Barrier  Vapour Barrier

Type of Insulation: Open Cell  Closed Cell  Color of SPF: \_\_\_\_\_

Confirm Water Vapour Permeance of the SPF Insulation is less than or equal to 60 ng/Pa.s.m<sub>2</sub> when tested in conformance with ASTM E 96 ( Y / N ) where SPF Insulation is to be used as the vapour barrier. Specify minimum thickness required for the product to attain this Water Vapour Permeance rating ( \_\_\_\_\_ inches).

Documentation submitted? Y / N (Documentation may be required)

Foamed plastics must be protected with a thermal barrier such as drywall or interior finish as defined by subsections 9.29.4 to 9.29.9 or have been tested in accordance with CAN4-S124-M and meet the requirements of classification B. (i.e.mineral wool insulation as tested)

Specify the thermal barrier that will be provided \_\_\_\_\_  
(Information on thermal barrier may be required to be submitted)

Plans/Details/Specifications reviewed and sealed by Professional Y / N

Spray-applied Polyurethane Foam Insulation to be applied to: (Specify location and thickness)

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Specify method of venting roof space if applicable: \_\_\_\_\_

\_\_\_\_\_

Job Site Address: \_\_\_\_\_

Licensed Contractor: \_\_\_\_\_ ID# \_\_\_\_\_

Certified Installer: \_\_\_\_\_ ID# \_\_\_\_\_

Signed by: \_\_\_\_\_  
PRINT NAME SIGNATURE

Address: \_\_\_\_\_ Phone: \_\_\_\_\_

It is the contractor's responsibility to ensure a label is placed on the job site as required by CAN/ULC-S705.2 including the above information and stating: "This certificate indicates that the installed spray-applied rigid polyurethane foam insulation meets the CAN/ULC-S705.1 – medium density – product standard. This product has been installed according to the CAN/ULC-S705.2 installation standard."